

# Schréder

## INDU BAY GEN3

### Emergency Box

#### SUPPLEMENTARY INSTALLATION INSTRUCTIONS




IEC EN 60598			
IP66		220-240V 50/60Hz	

<b>IK</b>
<b>08</b>


#### **WARNING**

1. Batteries should be stored within the specified temperature range in low humidity conditions.  
Optimal storage conditions are: Temperature: -20°C to +35°C Humidity: 45% - 85%
2. Avoid atmosphere with corrosive gas.
3. It is recommended to disconnect the battery before storage or delivery.
4. Battery should be charged once in three months in order to keeping it in initial performance.
5. This product should be installed by a full certified electrician in accordance with local building and electrical codes.


Emergency power	5 W	Operating voltage	220~240 V AC 50/60 Hz
Emergency time	180min	Working temperature	0°C ~ +50°C
IP rating	IP66	Battery capacity	3000 mAh



U-bracket  
Suspension chain




1



2

Activation  
(battery connection)




3


Permanent unswitched

AC INPUT


Suitable Wire  
diameter:  
φ5~φ11mm



4




5



6



## Mounting



### Pendant installation



### Suspension chain mounting



\*EM box electrified state

	Test Switch	EM Status
	Press	EM ON
	Don't Press	EM OFF

Indicator LED Status	Battery Status
Green Light	Charging
OFF	Discharging (Emergency mode)