

For installation of Startech 1-2 Bollard LED.
 Model. ST-10336, ST-10346, ST-10356, ST-10366, ST-70177 and ST-70187.

Product drawing (dimensions)

CE IP55 IK08 CLASS I

TOOL

1

ST-10336, ST-10346, ST-70177 ST-10356, ST-10366, ST-70187

2

Cable OD **2**
 Min. 6mm.
 Max. 12mm.
 Torque :10.5Nm.
 ~0.2m.
 ~6cm

3

4

Torque :0.25Nm.
 Torque :2.5Nm.
WARNING
 N ⊕ L
 3 4 2
 CABLE SIZE : 3x1.0mm²

Switch off mains power supply before joining the connectors

- LIGMAN standard products are supplied with the control gear 220-240V 50/60Hz. The control gear for other voltages and frequencies is available upon request, please consult us for more details.
- LIGMAN luminaire are designed to conform IEC 60598 2-1 standard.

Technical amendments and modifications techniques reserved.

Ligman Lighting

Europe Headquarters
 Ligman Europe s.r.o.
 VGP Park Usti nad Labem, P 2
 Prestanov 113
 403 17 Prestanov
 Czech Republic
 Tel. +420 608 740 504 | sales.cz@ligman.com

Thailand Headquarters
 Ligman Lighting Co., Ltd.
 17/2 Moo 4, Monthong, Bangnampreaw
 Chachoengsao 24150 Thailand
 Tel : +66 (2) 7339140
 info@ligman.com

Ligman SAS France
 7 rue Antoine Becquerel
 Centre d'activités Triasis
 31140, Launaguet
 Tel: +33 5 61 70 24 62
 sales.fr@ligman.com

