

**For Installation of Augusta 5 bollard.
Model. AUG-10011 and AUG-10012**

Product drawing (dimensions)
CE IP65 IK08 CLASS I

1

2

Cable OD
Min 6mm.
Max 12mm.

Torque :21.0Nm.

3

Torque :3.0Nm.

4

CABLE SIZE : 3x1.0mm²

L 2 N 3 PE 4

Torque :0.25Nm.

Torque :2.5Nm.

WARNING
Switch off mains power supply
before joining the connectors

5

Torque :3.0Nm.

6

- LIGMAN standard products are supplied with the control gear 220-240V 50/60Hz. The control gear for other voltages and frequencies is available upon request, please consult us for more details.
- LIGMAN luminaires are designed to conform IEC 60598 2-1 standard.

Technical amendments and modifications techniques reserved.

Ligman Lighting

<p>Europe Headquarters Ligman Europe s.r.o. VGP Park Usti nad Labem, P 2 Prestanov 113 403 17 Prestanov Czech Republic Tel. +420 608 740 504 sales.cz@ligman.com</p>	<p>Thailand Headquarters Ligman Lighting Co., Ltd. 17/2 Moo 4, Monthong, Bangnampreaw Chachoengsao 24150 Thailand Tel : +66 (2) 7339140 info@ligman.com</p>	<p>Ligman SAS France 7 rue Antoine Becquerel Centre d'activités Triasis 31140, Launaguet Tel: +33 5 61 70 24 62 sales.fr@ligman.com</p>
---	--	--