

For Installation of Concord 3 Bollard LED.
Model. CN-70156.

Product drawing (dimensions)

FLAT TOP
160
237

DOME TOP
160
258

TOOL
3

CE IP55 IK10 CLASS I

MOUNTING
150
62
35
Ø17
Ø55

①

②

Cable OD
Min. 6mm.
Max. 12mm.
Torque :10.5Nm.

~0.2m.

~3cm

③

④

N 3 L 2 4

Torque :0.25Nm.

Torque :2.5Nm.

WARNING

Switch off mains power supply
before joining the connectors

CABLE SIZE : 3x1.0mm²

20
6

- LIGMAN standard products are supplied with the control gear 220-240V 50/60Hz.
The control gear for other voltages and frequencies is available upon request, please consult us for more details.
- LIGMAN luminaires are designed to conform IEC 60598 2-1 standard.

Technical amendments and modifications techniques reserved.

Ligman Lighting

Europe Headquarters
Ligman Europe s.r.o.
VGP Park Usti nad Labem, P 2
Prestanov 113
403 17 Prestanov
Czech Republic
Tel. +420 608 740 504 | sales.cz@ligman.com

Thailand Headquarters
Ligman Lighting Co., Ltd.
17/2 Moo 4, Monthong, Bangnampreaw
Chachoengsao 24150 Thailand
Tel : +66 (2) 7339140
info@ligman.com

Ligman SAS France
7 rue Antoine Becquerel
Centre d'activités Triasis
31140, Launaguet
Tel: +33 5 61 70 24 62
sales.fr@ligman.com

