

**For Installation of VEKTER 3,4 BOLLARD.  
Model. VK-10001, VK-10002, VK-10011 and VK-10012**

**Product drawing (dimensions)**

**CE IP65 IK08 CLASS I**

**MOUNTING DETAIL**

**1**

**2**

Torque : 10.6Nm.

**3**

Torque : 4.3Nm.

CABLE SIZE : 3x1.0mm<sup>2</sup>

**4**

Torque : 2.0Nm.

Push  
 L = Line  
 ⊕ = Ground  
 N = Neutral

**5**

Torque : 3.0Nm.

**6**

- **LIGMAN standard products are supplied with the control gear 220-240V 50/60Hz.**  
The control gear for other voltages and frequencies is available upon request, please consult us for more details.
  - **LIGMAN luminaires are designed to conform IEC 60598 2-1 standard.**
- Technical amendments and modifications techniques reserved.

## Ligman Lighting

**Europe Headquarters**  
Ligman Europe s.r.o.  
VGP Park Usti nad Labem, P 2  
Prestanov 113  
403 17 Prestanov  
Czech Republic  
Tel. +420 608 740 504 | sales.cz@ligman.com

**Thailand Headquarters**  
Ligman Lighting Co., Ltd.  
17/2 Moo 4, Monthong, Bangnampreaw  
Chachoengsao 24150 Thailand  
Tel : +66 (2) 7339140  
info@ligman.com

**Ligman SAS France**  
7 rue Antoine Becquerel  
Centre d'activités Triasis  
31140, Launaguet  
Tel: +33 5 61 70 24 62  
sales.fr@ligman.com