

For Installation of Rado 5 bollard LED. Model. RA-10822

Product drawing (dimensions)

CE IP65 IK09 CLASS I

TOOL

1

MOUNTING DETAIL

2

Cable OD
Min. 6mm.
Max. 10mm.

Torque :10.5Nm.

~3cm.

3

4

Torque :0.25Nm.

Torque :2.5Nm.

N ⊕ L
3 4 2

WARNING

Switch off mains power supply
before joining the connectors

CABLE SIZE : 3x1.0mm²

- **LIGMAN standard products are supplied with the control gear 220-240V 50/60Hz.**
The control gear for other voltages and frequencies is available upon request, please consult us for more details.
- **LIGMAN luminaires are designed to conform IEC 60598 2-1 standard.**

Technical amendments and modifications techniques reserved.

Ligman Lighting

Europe Headquarters
Ligman Europe s.r.o.
VGP Park Usti nad Labem, P 2
Prestanov 113
403 17 Prestanov
Czech Republic
Tel. +420 608 740 504 | sales.cz@ligman.com

Thailand Headquarters
Ligman Lighting Co., Ltd.
17/2 Moo 4, Monthong, Bangnampreaw
Chachoengsao 24150 Thailand
Tel : +66 (2) 7339140
info@ligman.com

Ligman SAS France
7 rue Antoine Becquerel
Centre d'activités Triasis
31140, Launaguet
Tel: +33 5 61 70 24 62
sales.fr@ligman.com

