

LUNA





Mounting: On the ground Body material: $Aluminium \ and \ steel$

Standard gray RAL 9006, other RAL colours on request (please add RAL code after index number) Colour:

- 20°C ... +40°C

Philips / Osram or Tridonic LED module included LED module:

3000K or 4000K Colour temperature: Colour Rendering Index >80 in standard

Driver: Electronic driver

N/A Emergency unit: Movement sensor: N/A Daylight control sensor: N/A

Operating temperature

IP Class: IP65

Power: 220-240V 50/60Hz

Direct lighting Lighting direction:

Reflector type: N/A Light distribution: Symmetric

Clear tempered glass in standard, mat on request Diffusor:

General data: 5 Years standard warranty Three heights in standard 1000

mm / 1500 mm and 3000 mm

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used





Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Length [mm]	Weight [kg]
2989.3000/830/1M	3000	27	3000	Ra > 80	50.000	5	3	1000	10,00
2989.3000/840/1M	3000	27	4000	Ra > 80	50.000	5	3	1000	10,00
2989.3000/830/1,5M	3000	27	3000	Ra > 80	50.000	5	3	1500	13,00
2989.3000/840/1,5M	3000	27	4000	Ra > 80	50.000	5	3	1500	13,00
2989.3000/830/3M	3000	27	3000	Ra > 80	50.000	5	3	3000	22,00
2989.3000/840/3M	3000	27	4000	Ra > 80	50.000	5	3	3000	22,00

